



Specification	BigShot-HD PT	BigShot-HD PTZ 3X	BigShot-HD 3X Ultra	BigShot-HD PTZ 3X Wide	BigShot-HD PTZ 10X
List price	\$599.00	\$699.00	\$799.00	\$899.00	\$999.00
Video Output	USB 2.0 Plug & Play	USB 2.0 Plug & Play	USB 2.0 Plug & Play	USB 2.0 Plug & Play	USB 2.0 Plug & Play
Device Compatibility	All known PC's and Mobile Devices with USB connection	All known PC's and Mobile Devices with USB connection	All known PC's and Mobile Devices with USB connection	All known PC's and Mobile Devices with USB connection	All known PC's and Mobile Devices with USB connection
Pan/Tilt/FOV	P- 360°, T- 120°, FOV-140°	P- 360°, T- 120°, FOV-55°	P- 360°, T- 120°, FOV-41°	P- 360°, T- 120°, FOV-110°	P- 360°, T-120°, FOV-75°
Zoom	None - Pan & Tilt only	3X Optical	3X Optical	3X Optical	10X Optical
Image Sensor	1/3" CMOS High Speed with 1080p	1/3" CMOS High Speed with 720P	1/3" CMOS High Speed with 1080p	1/3" CMOS High Speed with 720P	1/3" CMOS High Speed with 720P
Focal Length	f=2.5mm, Wide Angle F1.8	f=3.8-38.0mm, F1.8	f=3.8-38.0mm, F1.8	f=2.5mm, Wide Angle F1.8	f=3.8-38.0mm, F1.8
Effective Pixels	1920 X 1080 Pixels	1080 X 720 Pixels	1920 X 1080 Pixels	1080 X 720 Pixels	1080 X 720 Pixels
Video Format	MJPEG - 1080P(1920*1080), 720P(1280*720),VGA(640*480),CIF(352*288)	MJPEG - 720P(1280*720),VGA(640*480),CIF(352*288)	MJPEG - 1080P(1920*1080), 720P(1280*720),VGA(640*480),CIF(352*288)	MJPEG - 720P(1280*720),VGA(640*480),CIF(352*288)	MJPEG - 720P(1280*720),VGA(640*480),CIF(352*288)
Focus	Auto	Auto & Manual	Auto & Manual	Auto & Manual	Auto & Manual
Preset Positions	10 Presets	10 Presets	10 Presets	10 Presets	10 Presets
Picture Effects	N/A	E-Flip, Invert, Mirror	E-Flip, Invert, Mirror	E-Flip, Invert, Mirror	E-Flip, Invert, Mirror
Remote Control Functions	IR Advanced Function Remote -Controls 4 cameras with Pan Tilt speed control, Presets	IR Advanced Function Remote -Controls 4 cameras with Pan Tilt speed control, Presets, Reverse PT, Reverse Image & Backlight Control	IR Advanced Function Remote -Controls 4 cameras with Pan Tilt speed control, Presets, Reverse PT, Reverse Image & Backlight Control	IR Advanced Function Remote -Controls 4 cameras with Pan Tilt speed control, Presets, Reverse PT, Reverse Image & Backlight Control	IR Advanced Function Remote -Controls 4 cameras with Pan Tilt speed control, Presets, Reverse PT, Reverse Image & Backlight Control
Mounting Options	Desktop, Wall, Tripod or Ceiling Mount	Desktop, Wall, Tripod or Ceiling Mount	Desktop, Wall, Tripod or Ceiling Mount	Desktop, Wall, Tripod or Ceiling Mount	Desktop, Wall, Tripod or Ceiling Mount
Minimum Illumination	Regular: 1Lux	Regular: 1Lux; Night: 0.1Lux(infra LED off),0Lux(infra LED on)	Regular: 1Lux; Night: 0.1Lux(infra LED off),0Lux(infra LED on)	Regular: 1Lux; Night: 0.1Lux(infra LED off),0Lux(infra LED on)	Regular: 1Lux; Night: 0.1Lux(infra LED off),0Lux(infra LED on)
Warranty	1 Year return to VueQuest	1 Year return to VueQuest	1 Year return to VueQuest	1 Year return to VueQuest	1 Year return to VueQuest
Communication Interface	EIA/RS-422, EIA/RS-232C	EIA/RS-422, EIA/RS-232C	EIA/RS-422, EIA/RS-232C	EIA/RS-422, EIA/RS-232C	EIA/RS-422, EIA/RS-232C
PTZ protocol	VISCA, Pelco P, Pelco D	VISCA, Pelco P, Pelco D	VISCA, Pelco P, Pelco D	VISCA, Pelco P, Pelco D	VISCA, Pelco P, Pelco D
Power	DC 12V+-10% ; 1.2A	DC 12V+-10% ; 1.2A	DC 12V+-10% ; 1.2A	DC 12V+-10% ; 1.2A	DC 12V+-10% ; 1.2A
Operating Temperature	0°C-+60°C, 0-95% RH	0°C-+60°C, 0-95% RH	0°C-+60°C, 0-95% RH	0°C-+60°C, 0-95% RH	0°C-+60°C, 0-95% RH
Camera Dimensions	9 1/2"W X 3 3/4"D X 5 3/4"H	9 1/2"W X 3 3/4"D X 5 3/4"H	9 1/2"W X 3 3/4"D X 5 3/4"H	9 1/2"W X 3 3/4"D X 5 3/4"H	9 1/2"W X 3 3/4"D X 5 3/4"H
Camera Weight	3.5 LBS	3.5 LBS	3.5 LBS	3.5 LBS	3.5 LBS
Included in Packaging (1 box)	Includes Camera, Remote, Power cord, Ceiling mount bracket, 16' USB Cable, Visca to RS232 cable Quick Start & User Manual	Includes Camera, Remote, Power cord, Ceiling mount bracket, 16' USB Cable, Visca to RS232 cable Quick Start & User Manual	Includes Camera, Remote, Power cord, Ceiling mount bracket, 16' USB Cable, Visca to RS232 cable Quick Start & User Manual	Includes Camera, Remote, Power cord, Ceiling mount bracket, 16' USB Cable, Visca to RS232 cable Quick Start & User Manual	Includes Camera, Remote, Power cord, Ceiling mount bracket, 16' USB Cable, Visca to RS232 cable Quick Start & User Manual
Packaging (1 Box)	13"W X 11 1/4"D X 5 1/4"H, 4LBS	13"W X 11 1/4"D X 5 1/4"H, 4LBS	13"W X 11 1/4"D X 5 1/4"H, 4LBS	13"W X 11 1/4"D X 5 1/4"H, 4LBS	13"W X 11 1/4"D X 5 1/4"H, 4LBS